



PLINTH AREA: 49.33 sq.m / 531 SQ.FT

SCHEDULE OF JOINERY

SL. NO.	TYPE	SIZE		SILL	TOP	DESCRIPTION	REMARKS
		WIDTH	HEIGHT				
1	D	1200	2100	-	2100	STEEL DOOR WITH 16GMS SHEET SHUTTER	TWO LEAVES
2	D1	900	2100	-	2100	STEEL DOOR WITH 18GMS SHEET SHUTTER	SINGLE LEAF
3	D2	750	2100	-	2100	PVC DOOR	SINGLE LEAF
4	W	1200	1300	800	2100	STEEL WINDOW WITH 18 GMS SHEET SHUTTERS & 12MM SQ. MS. BARS	TWO LEAVES
5	J	600	450	1650	2100	R.C.C. JOLLY	-
6	O	900	2000	-	2100	OPENING	-

IMPORTANT NOTES:

1. ECONOMICAL FOUNDATION MAY BE ADOPTED. DEPTH OF FOUNDATION SHOULD BE BASED ON THE SOIL CONDITION AT SITE.
2. FLOORING SHOULD BE DONE USING CERAMIC TILES
3. SILL SLAB(75mm THICK) SHOULD BE PROVIDED BELOW ALL WINDOW OPENINGS WITH 250 mm EXTENSION ON EITHER SIDE OF WINDOW OPENING.
4. PLINTH PROTECTION PLATFORM(750mm WIDE) SHOULD BE PROVIDED ALL-ROUND THE BUILDING
5. SLIGHT SLOPE SHOULD BE GIVEN FOR ROOF SLAB
6. WEATHERING COURSE SHOULD BE PROVIDED WITH REQUIRED SLOPE TO DRAIN RAIN WATER.
7. RWTH STRUCTURE SHOULD BE CONSTRUCTED AWAY FROM SEPTIC TANK(IF ANY) AND IT CAN BE LINKED TO A NEAR BY WATER SOURCE.
8. 110 mm OD PVC PIPES MAY BE USED FOR RAINWATER DOWNFALL PIPES

DRAWING NO:1-J18/SERD/Dt.03.09.11

DIRECTORATE OF RURAL DEVELOPMENT AND PANCHAYAT RAJ

SCALE 1:100 DATE ALL DIMENTIONS ARE IN mm.

AE AEE
EE SE
JOB NO:18 DRAWING NO:1

TYPE DESIGN FOR MILK PRODUCER'S COOPERATIVE SOCIETY BUILDING

PLAN, ELEVATION AND SECTION