



**ELEVATION**

**CROSS SECTION "A-A"**

**CROSS SECTION "BB"**

**PLAN**

**CROSS SECTION "CC"**

**TYPE - 4A**

**MINI COMMUNITY SANITARY COMPLEX FOR GIRLS (MIDDLE) WITH TOILET PROVISION FOR CHILDREN WITH SPECIAL NEEDS**

**IMPORTANT NOTES**

1. THE FLOORING SHOULD BE OF ANTI SKID NATURE TO AVOID SLIPPING
2. THE FLOORING MATERIAL SHOULD BE A CONTINUOUS SURFACE WITH MINIMUM SEALED JOINTS TO PREVENT ACCUMULATION OF DIRT.
3. SHARP CORNERS HAVE TO BE AVOIDED. OUT SIDE CORNERS HAVE TO BE CHAMFERED OR ROUNDED.
4. DOOR LATCH HEIGHT SHOULD NOT BE MORE THAN 730 MM
5. HOOKS SHOULD BE FIXED AT THE HEIGHT NOT MORE THAN 1575MM
6. A SMALL NICHE AT 571MM TO 600MM HEIGHT FROM THE FLOOR NEEDS TO BE PROVIDED TO PLACE FRESH SANITARY NAPKINS.
7. THE HEIGHT OF HAND WASH SHOULD NOT BE MORE THAN 780MM AND THE TAPS SHOULD BE FIXED AT 600MM INTERVAL
8. DUEL FLUSHING MECHANISM HAS TO BE PROVIDED FOR WATER CLOSET.
9. FLOOR DROP SHOULD NOT BE MORE THAN 6MM IN CASE OF TOILET FOR CHILDREN WITH SPECIAL NEEDS.
10. TOILET BASEMENT, SEPTIC TANK, LEACH PITS OR SOAK PITS MUST BE PROVIDED AS PER THE SOIL CONDITION OF THE PROPOSED SITE.
11. THE RAMP FLOOR OF THE TOILET FOR CHILDREN WITH SPECIAL NEEDS SHOULD BE ANTI SLIPPERY.
12. THE SLOPE INSIDE THE TOILET UNIT SHOULD BE TOWARDS THE TOILET SEAT TO DRAIN OFF WATER

AREA=238.55 Sqft

**SCHEDULE OF JOINERIES**

D	Door	0.90m x 2.10m
D1	Door 1	0.75m x 2.10m
J	Jolly	0.80m x 0.45m
SD	Sliding Door	1.20m x 2.10m