



**TYPE-3A
MINI COMMUNITY SANITARY COMPLEX FOR
GIRLS (ELEMENTARY) WITH TOILET PROVISION
FOR CHILDREN WITH SPECIAL NEEDS**

AREA=215.85 Sqft

SCHEDULE OF JOINERIES

GD Grill door	1.20m x 2.10m
SD Sliding Door	1.20m x 2.10m
D1 Door 1	0.75m x 2.10m
J Jolly	0.60m x 0.45m

IMPORTANT NOTES

1. THE FLOORING SHOULD BE OF ANTI SKID NATURE TO AVOID SLIPPING
2. THE FLOORING MATERIAL SHOULD BE A CONTINUOUS SURFACE WITH MINIMUM SEALED JOINTS TO PREVENT ACCUMULATION OF DIRT.
3. SHARP CORNERS HAVE TO BE AVOIDED. OUT SIDE CORNERS HAVE TO BE CHAMFERED OR ROUNDED.
4. DOOR LATCH HEIGHT SHOULD NOT BE MORE THAN 550 MM
5. THE HEIGHT OF HAND WASH SHOULD NOT BE MORE THAN 635MM AND THE TAPS SHOULD BE FIXED AT 600MM INTERVAL
6. PASSAGE ROOF SHOULD BE UV COATED POLYCARBONITE SHEET OF 12MM THICK
7. DUEL FLUSHING MECHANISM HAS TO BE PROVIDED FOR WATER CLOSET.
8. FLOOR DROP SHOULD NOT BE MORE THAN 6MM IN CASE OF TOILET FOR CHILDREN WITH SPECIAL NEEDS.
9. TOILET BASEMENT, SEPTIC TANK, LEACH PITS OR SOAK PITS MUST BE PROVIDED AS PER THE SOIL CONDITION OF THE PROPOSED SITE.
10. THE RAMP FLOOR OF THE TOILET FOR CHILDREN WITH SPECIAL NEEDS SHOULD BE ANTI SLIPPERY.
11. THE SLOPE INSIDE THE TOILET UNIT SHOULD BE TOWARDS THE TOILET SEAT TO DRAIN OFF WATER
12. A SMALL NICHE AT 571MM TO 600MM HEIGHT FROM THE FLOOR NEEDS TO BE PROVIDED TO PLACE FRESH SANITARY NAPKINS.